

BD - 0202A



Product Specifications :

1. LED downlight,
2. 1*1W, 80-100lm/w
3. CE&Rohs compliant.
4. Pure aluminum material, anodized finish
5. LED driver, input AC 85-264V 50Hz,
6. GS certified. output 350mA DC, free of voltage fluctuations.
7. Color temperature: 2700-4000 Warm white, 6000-6700 Cool white
8. Dimension: Dia80*38, Φ 60 mm
9. CRI 75-80

Features :

1. No multi shadow
2. Low power consumption
3. Long Lifespan (30 to 50k hrs)
4. No UV or hazardous materi
5. Excellent heat dissipation
6. Available in Warm & Cool white

BD - 0144A



Product Specifications :

1. LED downlight,
2. 1*1W, 80-100lm/w
3. CE&Rohs compliant.
4. Pure aluminum material, anodized finish
5. LED driver, input AC 85-264V 50Hz,
6. GS certified. output 350mA DC, free of voltage fluctuations.
7. Color temperature: 2700-4000 Warm white, 6000-6700 Cool white
8. Dimension: Dia 86mm*50mm
9. CRI 75-80

Features :

1. No multi shadow
2. Low power consumption
3. Long Lifespan (30 to 50k hrs)
4. No UV or hazardous material
5. Excellent heat dissipation
6. Available in Warm & Cool white

BD - 0146A



Product Specifications :

1. Commercial recessed LED downlight,
2. 3*1W, 80-100lm/w
3. CE&Rohs compliant.
4. Pure aluminum material, anodized finish
5. LED driver, input AC 85-264V 50Hz,
6. GS certified. output 350mA DC, free of voltage fluctuations.
7. Color temperature: 2700-4000 Warm white, 6000-6700 Cool white
8. Dimension: Dia 86mm*50mm
9. CRI 75-80

Features :

1. No multi shadow
2. Low power consumption
3. Long Lifespan (30 to 50k hrs)
4. No UV or hazardous material
5. Excellent heat dissipation
6. Available in Warm & Cool white

BD - 0176A



Product Specifications :

1. Recessed LED downlight,
2. 6*1W, 80-100lm/w
3. CE&Rohs compliant.
4. Pure aluminum material, anodized finish
5. LED driver, input AC 85-264V 50Hz,
6. GS certified. output 350mA DC, free of voltage fluctuations.
7. Color temperature: 2700-4000 Warm white, 6000-6700 Cool white
8. Dimension: Dia 109*38mm
9. CRI 75-80

Features :

1. No multi shadow
2. Low power consumption
3. Long Lifespan (30 to 50k hrs)
4. No UV or hazardous material
5. Excellent heat dissipation
6. Available in Warm & Cool white

BD - 0135A



Product Specifications :

1. Commercial recessed LED downlight,
2. 7*1W, 80-100lm/w
3. CE&Rohs compliant.
4. Pure aluminum material, anodized finish
5. LED driver, input AC 85-264V 50Hz,
6. GS certified. output 350mA DC, free of voltage fluctuations.
7. Color temperature: 2700-4000 Warm white, 6000-6700 Cool white
8. Dimension: Dia 105mm*H60mm
9. CRI 75-80

Features :

1. No multi shadow
2. Low power consumption
3. Long Lifespan (30 to 50k hrs)
4. No UV or hazardous material
5. Excellent heat dissipation
6. Available in Warm & Cool white

BD - 0136A



Product Specifications :

1. Commercial recessed LED Spotlight,
2. 9*1W, 80-100lm/w
3. CE&Rohs compliant.
4. Pure aluminum material, anodized finish
5. LED driver, input AC 85-264V 50Hz,
6. GS certified. output 350mA DC, free of voltage fluctuations.
7. Color temperature: 2700-4000 Warm white, 6000-6700 Cool white
8. Dimension: Dia 135mm*H45mm
9. CRI 74-90

Features :

1. Easy to install
2. Low power consumption
3. Lifespan more than 50k hrs
4. Shake proof
5. Excellent heat dissipation
6. Available in Warm & Cool white

BD - 0137A



Product Specifications :

1. Commercial recessed LED downlight,
2. 12*1W, 80-100lm/w
3. CE&Rohs compliant.
4. Pure aluminum material, anodized finish
5. LED driver, input AC 85-264V 50Hz,
6. GS certified. output 350mA DC, free of voltage fluctuations.
7. Color temperature: 2700-4000 Warm white, 6000-6700 Cool white
8. Dimension: Dia140*70, Φ 120 mm
9. CRI 75-80

Features :

1. No multi shadow
2. Low power consumption
3. Long Lifespan (30 to 50k hrs)
4. No UV or hazardous materi
5. Excellent heat dissipation
6. Available in Warm & Cool white

WALL LIGHTS


BD -2121A



Product Specifications :

2*5 W LED wall light, indoor wall light,
Size: W100*E80*H120mm
Warm white, 3000k
IP44

BD-2094A



Product Specifications :

1*3 W LED wall light, indoor wall light
Size: W100*E45*H100mm,
Warm white, 3000k
IP20


BD -2063A



Product Specifications :

3W LED indoor wall light,
Size: 170*E30*H170mm
Warm white, 3000k
IP20

BD - 2062A



Product Specifications :

8W LED wall light, indoor wall light
High power LED chips
Constant current LED drive.

LED DOWNLIGHT

BD -TD4 1*16W



Product Specifications :

- Well Qualified Outdoor Recessed Lighting,
- Light color: (3000--7000K, 75-95lm/w),
- With driver(Passed EMC and CE),
- Easy to install
- Available in Warm white
Cool white

LED PANEL LIGHT

BD - PLD 2 * 2 ft



Product Specifications :

Suspending, Embedding, Ceiling Mounting
Stable light and high color rendering index
Input AC 100-240
Cutting edge constant current driver with
High power efficiency
Available in **Cool white**

BD-BULB 1*7W



Product Specifications :

- Available both Dimmable and Non Dimmable
- Input AC 100-240 V,
- Compatible with standard E26/E27 base
- Adopt SMD LED as illuminant, high luminous efficiency
- Available in Warm white, Cool white

